



FLOOR

## SADDLE BROOK XT™

GLAZED PORCELAIN with REVEAL IMAGING®  
& STEPWISE™ TECHNOLOGY

 **daltile**®  
IMAGINE WHAT'S POSSIBLE™



Above and cover photos feature Oak Trail XT 6 x 36 field tile on the floor.

## The Greater Outdoors

Make the outdoors even more beautiful by extending the hardwood look of Saddle Brook™ to exterior spaces with Saddle Brook XT™. Designed to defeat exterior challenges, Saddle Brook XT features Daltile's innovative StepWise™ technology. This patent-pending process combines superior slip-resistance with optimum cleanability, giving commercial applications and outdoor floors the warmth and look of natural wood without the worry of moisture damage. Available in four rich colors, this versatile tile makes every outdoor space a breath of fresh air.

- **HARDWOOD MADE EASY**
  - Achieve the look of authentic hardwood in exterior spaces without the maintenance
  - Features Daltile's patent-pending StepWise technology for superior slip-resistance
  - Available in four natural wood colors to complement both modern and traditional décor



**PRE-CONSUMER  
RECYCLED MATERIALS**



**MADE IN THE U.S.A.**



**REVEAL IMAGING®**



**STEPWISE™**

All or select items within this series are made in the USA. For more information, visit [daltile.com/SaddleBrookXT](http://daltile.com/SaddleBrookXT).

**CERTIFIED**  
**PORCELAIN**  
**TILE**  
© 5% or less water absorption

# SADDLE BROOK XT™

GLAZED PORCELAIN with REVEAL IMAGING® & STEPWISE™ TECHNOLOGY

## FIELD TILE



OAK TRAIL XT SD83\*



FARMHOUSE XT SD84\*



WALNUT CREEK XT SD85\*




GRAVEL ROAD XT SD86\*

\* Also available in Saddle Brook SD13-16 for interior floor applications.

# SADDLE BROOK XT™

GLAZED PORCELAIN with REVEAL IMAGING® & STEPWISE™ TECHNOLOGY

## SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	6 x 36 Field Tile	(5-7/8" x 35-7/16") (15.00 cm x 90.00 cm)	5/16"	13.05	9

## FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1–2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit [www.daltile.com/dcof](http://www.daltile.com/dcof).


## OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	

## APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.


## TRIM

Type	Number	Size	Pieces per Carton
 Bullnose*	S-43H9	3 x 18	16

\* Bullnose stocked in Saddle Brook™ colors SD13- SD16. Colors SD13-SD16 coordinate with Saddle Brook XT™ colors SD83-SD86. Saddle Brook XT bullnose colors SD83-SD86 available by special order with extended lead time. Please specify Saddle Brook or Saddle Brook XT color designation when ordering bullnose trim tile.

Bullnose trim is intended to coordinate with field tile in the standard 90-degree installation position.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16" (overlap should not exceed 33% when installing rectangular size in a staggered brick-joint pattern)	 High (V3)

## TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	3-4

For additional information, visit [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## NOTES

Special consideration needs to be given when installing tiles 20" and larger. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at [daltile.com/Factors](http://daltile.com/Factors).

Saddle Brook XT™ includes StepWise™ technology and can be used on both interior and exterior floor applications. Saddle Brook™ does not include StepWise™ technology and can be used on interior floor applications only. For more information, visit [daltile.com/SaddleBrook](http://daltile.com/SaddleBrook).



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit [daltilegreenworks.com](http://daltilegreenworks.com).



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: [GET.DAL TILE.COM](http://GET.DAL TILE.COM)



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).



IMAGINE WHAT'S POSSIBLE™

©2016 Dal-Tile Corporation (3/16)